

SAFETY DATA SHEET

Date of issue/Date of revision

: 16 August 2022

Version

: 11.04



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : SIGMA MULTIPRIMER AQUA

Product code : 10100DN3191

Other means of identification

00359119; 00359120; 00359121; 00359122; 00359123; 00359124; 00398764; 00398765; 00398766; 00398773; 00398774; 00398775

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications, Application by non spray methods..

**Use of the substance/
mixture** : Coating.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Nederland B.V.
Amsterdamseweg 14
1422 AD Uithoorn
Netherlands
+31 (0)297 541234
Fax: +31 (0)297 541806

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

National contact

PPG Coatings Nederland B.V.
Amsterdamseweg 14
1422 AD Uithoorn
Netherlands
+31 (0)297 541234
Fax: +31 (0)297 541806

1.4 Emergency telephone number

National advisory body/Poison Centre

Nationaal Vergiftings Informatie Centrum 088 755 8000 (Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen)

Supplier

+31 (0)20 4075210

Code : 10100DN3191
SIGMA MULTIPRIMER AQUA

Date of issue/Date of revision : 16 August 2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : No signal word.

Hazard statements : Toxic to aquatic life with long lasting effects.

Precautionary statements

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Avoid release to the environment.

Response : Collect spillage.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
P102, P101, P273, P391, P501

Hazardous ingredients : Not applicable.

Supplemental label elements : Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one and octhiline (ISO). May produce an allergic reaction.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

Code : 10100DN3191 Date of issue/Date of revision : 16 August 2022
 SIGMA MULTIPRIMER AQUA

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % by weight | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|----------------------------------|-----------------------------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| zinc bis(orthophosphate) | REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6 | ≥1.0 - ≤4.9 | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M [Acute] = 1 M [Chronic] = 1 | [1] |
| (2-methoxymethylethoxy) propanol | REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8 | ≥1.0 - ≤5.0 | Not classified. | - | [2] |
| ammonium hydroxide | REACH #: 01-2119982985-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2 | ≤0.30 | Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 | STOT SE 3, H335: C ≥ 5% M [Acute] = 1 | [1] [2] |
| 1,2-benzisothiazol-3(2H)-one | EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 | <0.050 | Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 | ATE [Oral] = 1020 mg/kg ATE [Inhalation (dusts and mists)] = 0.4 mg/l Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1 | [1] |
| pyrithione zinc | REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7 | ≤0.019 | Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Oral] = 221 mg/kg ATE [Inhalation (dusts and mists)] = 0.14 mg/l M [Acute] = 1000 M [Chronic] = 10 | [1] |
| 2-methylisothiazol-3(2H)-one | REACH #: 01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9 | <0.0015 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 235 mg/kg ATE [Dermal] = 242 mg/kg ATE [Inhalation (dusts and mists)] = 0.19 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1 | [1] |
| octhilinone (ISO) | EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5 | <0.0010 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 | ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l | [1] |

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|--|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|--|
| | | | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above. | Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 | |
|--|--|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Code : 10100DN3191 Date of issue/Date of revision : 16 August 2022
SIGMA MULTIPRIMER AQUA

SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
phosphorus oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Exposure limit values |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (2-methoxymethylethoxy)propanol ammonium hydroxide | <p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 7/2021). ☐ OEL, 8-h TWA: 300 mg/m³ 8 hours.</p> <p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 7/2021). ☐ OEL, 8-h TWA: 14 mg/m³ 8 hours. STEL, 15-min: 36 mg/m³ 15 minutes.</p> |

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|---------------------------------|------|-----------------------|-------------------------|--------------------|----------|
| zinc bis(orthophosphate) | DNEL | Long term Oral | 0.83 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 2.5 mg/m ³ | General population | Systemic |
| propane-1,2-diol | DNEL | Long term Inhalation | 5 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 83 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 83 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 10 mg/m ³ | General population | Local |
| (2-methoxymethylethoxy)propanol | DNEL | Long term Inhalation | 10 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 50 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 168 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Oral | 0.33 mg/kg bw/day | General population | Systemic |
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Inhalation | 37.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 121 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 283 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 308 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 0.345 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.966 mg/kg bw/day | Workers | Systemic |
| pyrithione zinc | DNEL | Long term Inhalation | 1.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 6.81 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 0.01 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.021 mg/m ³ | General population | Local |
| 2-methylisothiazol-3(2H)-one | DNEL | Long term Inhalation | 0.021 mg/m ³ | Workers | Local |
| | DNEL | Long term Oral | 0.027 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 0.043 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 0.043 mg/m ³ | Workers | Local |
| | DNEL | Short term Oral | 0.053 mg/kg bw/day | General population | Systemic |

PNECs

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Type | Compartment Detail | Value | Method Detail |
|---------------------------------|------|------------------------|-----------------|--------------------------|
| trizinc bis(orthophosphate) | - | Fresh water | 20.6 µg/l | Sensitivity Distribution |
| | - | Marine water | 6.1 µg/l | Sensitivity Distribution |
| | - | Sewage Treatment Plant | 100 µg/l | Assessment Factors |
| | - | Fresh water sediment | 117.8 mg/kg dwt | Sensitivity Distribution |
| | - | Marine water sediment | 56.5 mg/kg dwt | Equilibrium Partitioning |
| propane-1,2-diol | - | Soil | 35.6 mg/kg dwt | Sensitivity Distribution |
| | - | Fresh water | 260 mg/l | Assessment Factors |
| | - | Marine water | 26 mg/l | Assessment Factors |
| | - | Sewage Treatment Plant | 20000 mg/l | Assessment Factors |
| | - | Fresh water sediment | 572 mg/kg dwt | Equilibrium Partitioning |
| (2-methoxymethylethoxy)propanol | - | Marine water sediment | 57.2 mg/kg dwt | Equilibrium Partitioning |
| | - | Soil | 50 mg/kg dwt | Equilibrium Partitioning |
| | - | Fresh water | 19 mg/l | Assessment Factors |
| | - | Marine water | 1.9 mg/l | Assessment Factors |
| | - | Sewage Treatment Plant | 4168 mg/l | Assessment Factors |
| | - | Fresh water sediment | 70.2 mg/kg | Equilibrium Partitioning |
| | - | Marine water sediment | 7.02 mg/kg | Equilibrium Partitioning |
| | - | Soil | 2.74 mg/kg | Equilibrium Partitioning |

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : For prolonged or repeated handling, use the following type of gloves:

Recommended: Chloroprene, butyl rubber, nitrile rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Faint odour.
- Odour threshold** : Not available.
- Melting point/freezing point** : May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -4.79°C (23.4°F)
- Initial boiling point and boiling range** : 100°C
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Not applicable.
- Flash point** : Closed cup: Not applicable. [Product does not sustain combustion.]
- Auto-ignition temperature** :

| Ingredient name | °C | °F | Method |
|---------------------------------|-----|-------|---------|
| (2-methoxymethylethoxy)propanol | 207 | 404.6 | EU A.15 |

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : 8.8
- Viscosity** : Kinematic (40°C): >21 mm²/s
- Solubility(ies)** :

| Media | Result |
|------------|-------------------|
| cold water | Partially soluble |

Partition coefficient: n-octanol/water : Not applicable.

Vapour pressure :

Code : 10100DN3191
SIGMA MULTIPRIMER AQUA

Date of issue/Date of revision : 16 August 2022

SECTION 9: Physical and chemical properties

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| water | 23.8 | 3.2 | | | | |

- Evaporation rate** : Highest known value: 0.02 ((2-methoxymethylethoxy)propanol) Weighted average: 0.01 compared with butyl acetate
- Relative density** : 1.28
- Vapour density** : Highest known value: 5.1 (Air = 1) ((2-methoxymethylethoxy)propanol). Weighted average: 3.67 (Air = 1)
- Explosive properties** : Not available.
- Oxidising properties** : Product does not present an oxidizing hazard.

Particle characteristics

- Median particle size** : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---------------------------------|---------------------------------|---------|-------------|----------|
| zinc bis(orthophosphate) | LC50 Inhalation Dusts and mists | Rat | >5.7 mg/l | 4 hours |
| propane-1,2-diol | LD50 Oral | Rat | >5000 mg/kg | - |
| | LD50 Dermal | Rabbit | 20800 mg/kg | - |
| (2-methoxymethylethoxy)propanol | LD50 Oral | Rat | 20 g/kg | - |
| | LC50 Inhalation Vapour | Rat | 500 ppm | 4 hours |
| | LD50 Dermal | Rabbit | 9.5 g/kg | - |
| ammonium hydroxide | LD50 Oral | Rat | 5.23 g/kg | - |
| | LD50 Oral | Rat | 350 mg/kg | - |

English (GB)

Netherlands

10/17

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 11: Toxicological information

| | | | | |
|------------------------------|---------------------------------|------------|------------|---------|
| 1,2-benzisothiazol-3(2H)-one | LC50 Inhalation Dusts and mists | Rat | 0.4 mg/l | 4 hours |
| pyrithione zinc | LD50 Oral | Rat | 1020 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | 0.14 mg/l | 4 hours |
| 2-methylisothiazol-3(2H)-one | LD50 Dermal | Rabbit | >2 g/kg | - |
| | LD50 Oral | Rat | 177 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | 0.19 mg/l | 4 hours |
| octhiline (ISO) | LD50 Dermal | Rat | 242 mg/kg | - |
| | LD50 Oral | Rat - Male | 235 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | 0.27 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 311 mg/kg | - |
| | LD50 Oral | Rat | 125 mg/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|-----------------------|---------|-------|----------|-------------|
| pyrithione zinc | Eyes - Cornea opacity | Rabbit | 4 | 24 hours | 24 hours |

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

| Product/ingredient name | Route of exposure | Species | Result |
|------------------------------|-------------------|------------|-------------|
| 1,2-benzisothiazol-3(2H)-one | skin | Guinea pig | Sensitising |
| octhiline (ISO) | skin | Mouse | Sensitising |

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| ammonium hydroxide | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 11: Toxicological information

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| pyrithione zinc | Category 1 | - | - |

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking

Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Code : 10100DN3191 Date of issue/Date of revision : 16 August 2022
 SIGMA MULTIPRIMER AQUA

SECTION 11: Toxicological information

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------------|----------|
| zinc bis(orthophosphate) propane-1,2-diol (2-methoxymethylethoxy)propanol 1,2-benzisothiazol-3(2H)-one pyrithione zinc | Acute LC50 0.112 mg/l | Fish | 96 hours |
| | Chronic NOEC 0.026 mg/l | Fish | 30 days |
| | Acute LC50 40613 mg/l | Fish | 96 hours |
| | Acute EC50 1919 mg/l | Daphnia | 48 hours |
| | Acute EC50 0.11 mg/l | Algae | 72 hours |
| | Chronic NOEC 0.09 mg/l | Fish | 28 days |
| | Acute EC50 5.513 µg/l | Algae - Nitzschia pungens | 96 hours |
| | Marine water | | |
| | Acute LC50 0.0082 mg/l | Daphnia | 48 hours |
| | Chronic NOEC 1.889 µg/l | Algae - Nitzschia pungens | 96 hours |
| Marine water | | | |
| Chronic NOEC 0.0027 mg/l | Daphnia | 21 days | |

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|-------------------------|------|----------------|------|----------|
| pyrithione zinc | - | 39 % - 28 days | - | - |

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|------------------------------|-------------------|------------------|------------------|
| propane-1,2-diol | - | - | Readily |
| 1,2-benzisothiazol-3(2H)-one | - | - | Readily |
| pyrithione zinc | - | 50%; < 28 day(s) | Not readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---------------------------------|--------------------|-----|-----------|
| propane-1,2-diol | -1.07 | - | low |
| (2-methoxymethylethoxy)propanol | 0.004 | - | low |
| 1,2-benzisothiazol-3(2H)-one | 0.7 | - | low |
| pyrithione zinc | 0.9 | 0.9 | low |
| octhilonone (ISO) | 2.45 | - | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Code : 10100DN3191 Date of issue/Date of revision : 16 August 2022
 SIGMA MULTIPRIMER AQUA

SECTION 12: Ecological information

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|-----------------------------------------------------------------------------------|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container | 15 01 06 mixed packaging |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| | ADR/RID | ADN | IMDG | IATA |
|----------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 14.1 UN number or ID number | UN3082 | UN3082 | UN3082 | UN3082 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate)) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate)) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate)) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate)) |
| 14.3 Transport hazard class(es) | 9 | 9 | 9 | 9 |
| 14.4 Packing group | III | III | III | III |

Code : 10100DN3191 Date of issue/Date of revision : 16 August 2022
SIGMA MULTIPRIMER AQUA

14. Transport information

| 14.5 Environmental hazards | Yes. | Yes. | Yes. | Yes. |
|-----------------------------|-----------------|-----------------|--------------------------------|-----------------|
| Marine pollutant substances | Not applicable. | Not applicable. | (trizinc bis (orthophosphate)) | Not applicable. |

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Tunnel code : (-)

ADN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

VOC for Ready-for-Use Mixture : A/i. One-pack performance coatings. EU limit values: 140 g/l (2010.)
This product contains a maximum of 70 g/l VOC.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

E2

Code : 10100DN3191 Date of issue/Date of revision : 16 August 2022
 SIGMA MULTIPRIMER AQUA

SECTION 15: Regulatory information

| Product/ingredient name | List name | Name on list | Classification | Notes |
|-------------------------|-------------------------------------|---------------------------------------------------------------------------------------|------------------------------------|-------|
| pyrithione zinc | Netherlands Reprotoxic Chemicals | pyrithionzink; (T-4)-bis [1-(hydroxy-κ-O) pyridine-2-(1H)- thionato-κ-S]zink | Dev. development category 1B | - |

National regulations

Water Discharge Policy (ABM) : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioaccumulative potential/ toxicity or persistence). Decontamination effort: Z

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 PBT = Persistent, Bioaccumulative and Toxic
 vPvB = Very Persistent and Very Bioaccumulative
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 IMDG = International Maritime Dangerous Goods
 IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|--------------------|
| Aquatic Chronic 2, H411 | Calculation method |

Full text of abbreviated H statements

| | |
|--------|-----------------------------------------------------------------|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H335 | May cause respiratory irritation. |
| H360D | May damage the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

Code : 10100DN3191

Date of issue/Date of revision

: 16 August 2022

SIGMA MULTIPRIMER AQUA

SECTION 16: Other information

| | |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 2 | ACUTE TOXICITY - Category 2 |
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Repr. 1B | REPRODUCTIVE TOXICITY - Category 1B |
| Skin Corr. 1 | SKIN CORROSION/IRRITATION - Category 1 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

History

Date of issue/ Date of revision : 16 August 2022

Date of previous issue : 28 January 2022

Prepared by : EHS

Version : 11.04

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.